

Prime Power Genset rating at 0.8 pf (kVA / KW)	Genset Model	Engine Model	Engine Power at 1500 rpm. kW (hp)	Current Rated (Amps) @ 100%	Fuel Tank Capacity (Ltr)	Lub Oil Sump Cap. (Ltr)	Overall Canopy Dimensions L x W x H (mm)	Approx. weight (with canopy) kg.
Air Cooled Gensets								
3	KCC-PE-2800 AS	CCP196	3.67 / 5	12.2	1.3	0.6	820 x 480 x 630	83
7.5 / 6	KG4-7.5SAS1	EA10NA 4G1	7.3 / 10	30 / 10	50	5	1310 x 810 x 1600	670
Liquid (Radiator) Cooled Gensets								
7.5 / 6	KG4-7.5WS1	2R550NA 4G1	7.9 / 10.74	30 / 10	28	3.8	1600 x 760 x 1050	550
10 / 8	KG4-10WS1	3R550NA 4G1	11 / 15	40 / 13.3	32	5.95	1800 x 760 x 1050	590
15 / 12	KG4-15WS1	3R550TC 4G1	15.4 / 20.9	60 / 20	32	5.95	1850 x 760 x 1050	610
20 / 16	KG4-20WS1	3R550TA 4G1	18.8 / 25.5	80 / 26.6	40	5.95	2180 x 905 x 1150	690
25 / 20	KG4-25WS1	3R550ETA 4G1	26.5 / 36	100 / 33.3	50	5.95	2330 x 950 x 1260	780
30 / 24	KG4-30WS1	3R1190ENA 4G1	31 / 42	120 / 40	72	7	2500 x 950 x 1385	1040
40 / 32	KG4-40WS1	3R1190ETA 4G1	41.1 / 56	53.3	100	7	2750 x 1050 x 1495	1180
58.5 / 46.8	KG4-58.5WS	4R810ETA 4G1	54.4 / 74	78	165	10	2900 x 1100 x 1580	1485
82.5 / 66	KG4-82.5WS1	4R1190ETA 4G1	77.2 / 105	110	200	10	3200 x 1350 x 1595	1860
100 / 80	KG4-100WS1	4K1080ETA 4G1	114.7 / 156	133.3	230	14	3200 x 1350 x 1800	2230
125 / 100	KG4-125WS1	4K1080ETA 4G1	114.7 / 156	166.6	230	14	3200 x 1350 x 1800	2260
160 / 128	KG4-160WS11	6K1080ETA 4G1	147.1 / 200	213.3	400	25	4200 x 1450 x 1900	3050
200 / 160	KG4-200WS1	6K1080ETA 4G2	183.8 / 250	266.6	400	25	4200 x 1450 x 1900	3150
200 HD / 160	KG4-200WS1	6SL90ETA 4G1	183.8 / 250	266.6	460	27	4550 x 1700 x 2005	3960
250 / 200	KG4-250WS1	6SL90ETA 4G2	228 / 310	333.3	600	27	4750 x 1700 x 2005	4100
320 / 256	KG4-320WS1	6SL90ETA 4G3	279.5 / 380	426.6	600	27	4750 x 1700 x 2005	4200
320 HD / 256	KG4-320WS HD	DV8ETA 4G1	294.2 / 400	426.6	600	40	5100 x 2125 x 2610	6950
400 / 320	KG4-400WS11	DV8ETA 4G2	360 / 490	533.3	850	40	5575 x 2125 x 2610	7150
500 / 400	KG4-500WS	DV8ETA 4G3	447.2 / 608	666.6	850	40	5575 x 2125 x 2610	7400
500 HD / 400	KG4-500WS HD	DV10ETA 4G1	447.2 / 608	666.6	990	50	6500 x 2125 x 2710	8360
625 / 500	KG4-625WS	DV10ETA 4G2	561.1 / 763	833.3	990	50	6500 x 2125 x 2710	8450
625 HD / 500	KG4-625WS11	DV12ETA 4G1	561.1 / 763	833.3	990	73	6800 x 2300 x 2715	9600
750 / 600	KG4-750WS	DV12ETA 4G2	662 / 900.6	1000	990	73	6800 x 2300 x 2715	9700
HHP Series								
900 HD / 720	KG1 - 900WS	DV16ETAG2	799 (1087)	1210	990	130	8000 x 2300 x 2713	13600
1010 HD / 808	KG1 - 1010WS	DV16ETAG1	889 (1210)	1346	990	130	7800 x 2300 x 2713	13200
1250 HD / 1000	KG1 - 1250WS	12K4300-E2	1090 (1489)	1166	880	265	5650 x 2300 x 2680	13075
1500 HD / 1200	KG1 - 1500WS	12K4300-E1	1294 (1760)	2000	880	265	5650 x 2300 x 2680	13075

Notes

Above specifications are subject to change without prior notice due to continuous technical development.
 For intermediate ratings, kindly contact nearest Kirloskar Office.
 For Site conditions other than standard operating conditions, consult Kirloskar Oil Engines for available prime power.

We offer products for every segment & take part in the India's growth story.



Infrastructure



Industry



IT/ITES



Hospitality



Health



Realty



Government



Logistics

