



JARVIS U3

Speaker Tracking Camera

JARVIS U3

SPECIFICATION



Camera	
Image Sensor	1/2.8" CMOS,2MP
Focal Lens	f=3.9mm - 46.8mm
Zoom	Optical: 12X, Digital: 12X
Iris	F1.6 - F2.8
FOV	72.5°
Other Functions	Speaker Tracking, Auto Framing
Focus System	Auto, Manual, PTZ Push, One Push
Shutter Speed	1/25 - 1/10,000s
AGC	Auto, Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Tracking
Exposure Control	Auto, Manual, Shutter Priority, Iris Priority
S/N Ratio	>50dB
BLC	YES

Full View Camera	
Image Sensor	1/2.5"4K CMOS Sensor, 8.57 MP
Lens	2.8mm focus,4X digital zoom
FOV	98°
DNR	2D/3D
Video Adjustment	Support ePTZ

PTZ	
Pan	-90° ~ +90°, 0.1°/s ~ 100°/s
Tilt	-30° ~ +90°, 0.1°/s ~ 80°/s
Preset Number	64

Network	
Max Image Size	1920x1080@60fps
Video Compression	H.264/ H.265/MJPEG
Audio Compression	AAC
Protocol	ONVIF, RTSP, RTMP,RTP HTTP, TCP, UDP
Multi Stream	Support 1x close-up view 1x full view,1x switching

Inteface	
SDI	1x3G-SDI,Video Format : 1080pp60/50/30/25,720p60/50
HDMI	1xHDMI,Video Format : 1080pp60/50/30/25,720p60/50
USB	1xUSB 2.0
Audio Input	3.5mm LINE IN ,including one channel echo cancellation reference audio
Network Interface	RJ45

General	
Protocols	VISCA
Address	1-6
Power	DC12V
Power Consumption	<20W
Operating Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +60°C
Operating Humidity	10% RH ~ 90% RH
Dimensions (LxWxH)	245mm × 145mm × 165mm
Weight	3.4kg

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net