



CP 19CA

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The automatic strapping machine CP 19CA is suitable for strapping various packages or boxes. The machine is able to process PP strap of 9 or 12 mm and has a very simple control panel. The CP 19CA is also mobile because of the swivel wheels. The strapping machine can make up to 30-32 strappings per minute, depending on the set tension, package size and arch size. This makes the CP 19CA ideal as a starter in automatic strapping.

Advantages

- For PP strap of 9 or 19 mm, thickness from 0.6 mm
- Automatic belt insertion and ejection
- Easy operation
- Electronic tension control
- Built-in photo sensor for automatic strapping
- Mobile, equipped with foot pedal
- Various arch sizes available



Technical specifications:	
Min. package size	200 x 750 x 500 mm (L x W x H)
Strapping material	Polystrap 9 or 19 mm
Strap coil	Core diameter 200 mm, Outer diameter 400 mm, Width 160 mm
Strap tension	70 - 882 N ~90 Kgs.
Sealing method	Hotseal
Noise	~ 75 dB(A)
Warm up time	Approximately 1 min
Power	230 V, 50 Hz
Machine weight	Approximately 220 kg
Operating temperature	5 - 40 °C



PackAuto Innovation Ind. Pvt. Ltd.
1A, Road No. 1, VKIA, Jaipur, Rajasthan - 302013

✉ packautoinnovation@gmail.com
sales@packautoinnovation.com

☎ +91-9509255931 , 9873549391

🌐 www.packautoinnovation.com